


PIŁY TARCZOWE DO DREWNA

	D	B	b	d	Z	Kąt natarcia A1	Jakość cięcia wzdłuż włókien	Jakość cięcia w poprzek włókien	NL	Kod Freud	Nr art.
	mm	mm	mm	mm							
	160	2,2	1,6	20	48	5°	•	•••	2/6/32,5	FR06W008H	F03FS09680
	165	1,5	1,0	20	12	25°	•••	•	-	FR07W009HC	F03FS10051
	165	1,5	1,0	20	24	25°	•••	•	-	FR07W010HC	F03FS10052
	165	1,5	1,0	20	36	15°	••	••	-	FR07W011HC	F03FS10053
	165	1,5	1,0	20	48	10°	•	•••	-	FR07W012HC	F03FS10054
	165	1,7	1,3	20	12	20°	•••	•	-	FR07W009H	F03FS10040
	165	1,7	1,3	20	24	15°	•••	•	-	FR07W001H	F03FS09686
	165	1,7	1,3	20	40	18°	•	•••	-	FR07W002H	F03FS09687
	182	1,7	1,3	19,05	30	15°	•••	•	-	FR10W001H	F03FS09700
	182	1,7	1,3	19,05	40	15°	••	••	-	FR10W002H	F03FS09701
	182	1,7	1,3	19,05	60	15°	•	•••	-	FR10W003H	F03FS09702
	184	1,6	1,0	20	24	25°	•••	•	-	FR11W010HC	F03FS10055
	184	1,6	1,0	20	48	10°	•	•••	-	FR11W011HC	F03FS10056
	190	1,5	1,0	30	18	25°	•••	•	-	FR13W010HC	F03FS10057
	190	1,5	1,0	30	24	25°	•••	•	-	FR13W011HC	F03FS10058
	190	1,5	1,0	30	48	15°	••	••	-	FR13W012HC	F03FS10059
	190	1,5	1,0	30	60	10°	•	•••	-	FR13W013HC	F03FS10060



Maszyny:
Uciosarki.


Materiały:
Drewno lite – miękkie i twarde, płyty wiórowe, sklejka, płyty MDF oraz inne materiały drewnopochodne.

Informacje techniczne:
Ząb ATB z ujemnym kątem natarcia.

Do uciosarek



Uciosarki



Przewodowe



Drewno miękkie



Drewno twarde



Płyta wiórowa



Sklejka



Płyta MDF

D	B	b	d	Z	Kąt natarcia A1	NL	Kod Freud	Nr art.
mm	mm	mm	mm					
210	2,4	1,8	25,4	24	-5°	-	FR15W002M	F03FS11566
210	2,4	1,8	25,4	48	-5°	-	FR15W003M	F03FS11517
210	2,4	1,8	30	48	-5°	2/7/42	FR15W001M	F03FS09747
216	2,4	1,8	25,4	48	-5°	2/6/42	FR16W004M	F03FS09751
216	2,4	1,8	25,4	64	-5°	2/6/42	FR16W005M	F03FS09752
216	2,4	1,8	30	24	-5°	2/6/42	FR16W001M	F03FS09748
216	2,4	1,8	30	40	-5°	2/7/42	FR16W002M	F03FS09749
216	2,4	1,8	30	48	-5°	2/7/42	FR16W003M	F03FS09750
250	2,4	1,8	30	40	-5°	FT121	FR23W001M	F03FS09753
250	2,4	1,8	30	60	-5°	FT121	FR23W002M	F03FS09754
254	2,4	1,8	30	60	-5°	FT121	FR24W001M	F03FS09755
260	2,4	1,8	30	60	-5°	FT121	FR26W001M	F03FS09760
300	2,4	1,8	30	72	-5°	FT121	FR28W001M	F03FS09761
305	2,4	1,8	30	48	-5°	-	FR29W001M	F03FS09762
305	2,4	1,8	30	72	-5°	FT121	FR29W002M	F03FS09763
315	2,4	1,8	30	72	-5°	FT121	FR30W001M	F03FS09766

FT121: 2/7/42 + 2/9/46 + 2/9,5/46,5 + 2/10/60